



## Technical data **MobiMASTER ICU 602**

<b>Operating voltage</b>	24 VDC (9 - 36 VDC)
<b>Power consumption</b>	max. 0.2 A at 24 VDC
<b>Operating temperature</b>	- 25 °C to + 70 °C
<b>Display</b>	LCD graphic display, 64 x 256 pixels
<b>Dimensions</b>	178 x 50 x 115 (L x H x D, installation dimensions in mm without front panel)
<b>Weight</b>	620 g
<b>Interfaces</b>	<b>standard:</b> RS485, digital I/O, RS232, USB <b>optional:</b> IBIS Slave, IBIS Master, GPS, Ethernet, Audio
<b>Editing software</b>	MIE (MobilInfoEdit)
<b>Data update</b>	<b>manually</b> via USB flash memory <b>automatically</b> via IP/Ethernet Interface (wireless and FTP service optionally available)
<b>Memory capacity</b>	256 MB
<b>Standards and directives</b>	<b>EMC</b> ECE-R10, Rev. 04 (EMC-Bus) Type approval number: (E5) 10R-04178  <b>Flammability</b> Directive 95/28/EC Regulation ECE-R118

**Modern design.**

**Alphanumeric keyboard with highly user-friendly buttons and backlight.**

**IP classified front (dust and water protected), optionally also IP classified from the back.**

**Advanced version includes:**

- Next stop information
- Voice announcement function for announcements inside and outside the vehicle
- GPS receiver
- Ethernet Interface
- Automatic triggering via GPS or odometer

**Fits into a standard radio slot (ISO 7736).**